Order Form - Progeo *VARIO CARBON*

Date .....

User .....

End user wheight (kg) .....

Language user manual .....

Progeo (English)

Company stamp

Responsible .....

Folding frame wheelchair

Wheelchair measures - The tolerance on all the dimensions indicated and/or required is ± 10 mm

Seat width (LS) ☐ 33 ☐ 36 ☐ 39 ☐ 42 ☐ 45 ☐ 48

Seat depth (PS) ☐ 35 ☐ 37,5 ☐ 40 ☐ 42,5 ☐ 45 ☐ 47,5

The real seat depth, from the front part of the seat cloth to the backrest tube will be 1 cm more than the declared one.

Footplate distance (DP) ..... (cm) ±0.5cm - adjustment steps 1.5cm

(Real distance between seat and footplate) - IMPORTANT NOTICE! From the footplate to the floor minimum 4cm !! (Minimum Front height = DP + 4cm)

Setting ☆ Standard ☐ Prudential ☐ Active ☐ Extreme


Backrest Height (TS) Std.Value 36 .....(min 30-max 54) adjustment steps 1.5cm

Crossbrace (black) ☆ Single ☐ Double (Not seat width 33-36)

Rear wheel camber ☆ 0° ☐ 2° ☐ 4°

Front height ..... (STD 49) - Rear height ..... (STD 44)

Carbon fibre frame - Opaque transparent painting




☐ Short frame - Ideal with Seat depth (PS) 35 - 37,5

☐ Medium frame - Ideal with Seat depth (PS) 40 - 42,5

☐ Long frame - Ideal with Seat depth (PS) 45 - 47,5

Front frame angle



Colour set: Rear wheels, wheel plates and forks - To be matched only with: Rear wheels Ultra-light Progeo - Standard!

☆ Black	22" 24" 25" 26"	
○ Bright silver	22" 24"	00833
○ Bright fuchsia	22" 24"	00833
○ Bright blue	22" 24"	00833
○ Bright red	22" 24"	00833
○ Bright lime	22" 24"	00833
○ Pearl white	22" 24"	00833

Adjustable velcro straps and padded transpiring upholstery

☆ Adjustable velcro straps and padded transpiring upholstery

Handle tube

☆ Tubes with standard handle

☐ Tubes with short handle

○ Folding handles 02958

Not available with: Push handles for companion, Brake handles for companion (Drum Brake)

Casters

☆ 5" Soft

☐ 4" Soft

☐ 3" Sport

☐ 6" Soft Not available with frame angle 95°

☐ 6" Pneumatic Not available with frame angle 95°

○ 3" Active Soft (wide)	(Aluminium alloy rim)	06824
○ 4" Active Sport (narrow)	(Aluminium alloy rim)	01398
○ 4" Active Soft (wide)	(Aluminium alloy rim)	03943
○ 5" Active Soft (wide)	(Aluminium alloy rim)	07518
○ 5" Pneumatic		10844

Date ..... Order ..... User ..... Address .....

Rear wheels

☆ 24" Ultra-light Progeo - Standard!

☐ 22" Ultra-light Progeo - Standard!

☐ 25" Ultra-light Progeo - Standard! **(colour: black)**

☐ 26" Progeo - Standard! **(colour: black)**

○ 24" ULTRA-LIGHT PROGEO KEY SPORT	**Weight reduction approx. 450gr.**		04383
○ 24" Ultra-light "Spinergy LX"			01685
○ 24" Ultra-light "Spinergy LXL"	☐ Black hub and white spokes	☐ Hub and spokes black	07846
○ 24" Ultra-light "Spinergy Flex rim"	**Integrated aluminium/rubber handrim**		02270
○ 25" Ultra-light "Spinergy LX"			02101
○ 25" Ultra-light "Spinergy LXL"	☐ Black hub and white spokes		07847
○ 26" Ultra-light "Spinergy LX"			02102
○ 24" Off-road (aluminium handrim black)			01392
○ 22" with brake handles for companion (drum brake) (aluminium handrim) **Available only with camber 0°**			03385
○ 24" with brake handles for companion (drum brake) (aluminium handrim) **Available only with camber 0°**			03384
○ One arm drive - (24" rear wheels Aluminium handrim High pressure Tyre) - camber 0°	○ Right ○ Left		02103

Rear wheel tyre

☆ High pressure tyre	(22"-24"-25"-26")		
☐ High pressure profile tyre	(24")		
○ Marathon Plus	(24"-25")	with anti-puncture protection	01669
○ Anti-puncture - Colour Black	(24")		11083
Not available with Rear wheels : 24" ULTRA-LIGHT PROGEO KEY SPORT, 24" Ultra-light "Spinergy LXL"			
○ Anti-puncture - Colour Grey	(22")		04181

Handrim — Wheel distance ☆ 3 cm ☐ 4 cm

☆ Aluminium	(22"-24"-25"-26")		
○ Aluminium black SOFT-TOUCH	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	09170
○ Chromed Steel	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	01684
○ Titanium	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	00016
○ Ultra Grepp	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	00017
○ Max Grepp	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	00834
○ Ergo Para	(24")		00632
○ TOP FRICTION **Oval countour with a rubber insert**	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	11023
○ NOVA H **Ergonomic black profile**	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	11025
○ NOVA D **Ergonomic profile with rubber coating (ideal for quadriplegics)**	(24"-25")	(24" handrim, on 25" wheel is installed with spacers)	11026
○ SURGE LT	(25")	**Oval countour with a rubber insert**	06427
○ Quad	(24")		00693
○ Silicon cover for standard aluminium handrim		Available for measures (22"- 24" - 26")	04050

Wheel locks

☆ Bent lever push to lock



☐ Straight lever push to lock
☐ Straight lever pull to lock



○ Sport brake



06428

○ Brake with extension lever push to lock



01949

○ Brake with extension lever pull to lock

03372

Date ..... Order ..... User ..... Address .....


Footplate - See reference tables N°3

☆ Plastic footrest, rake adjustable
Not available with Elevating front frame, swing away and removable
Minimum footplate distance 31cm ☆ 2/3 Internal ☐ 2/3 External



11525


☐ One piece footplate - Flip-up! rake and depth adjustable
Not available with Elevating front frame, swing away and removable
Minimum footplate distance 29cm ☐ Internal ☆ 2/3 Internal ☐ External



11527


O Minimum footplate distance 24cm. Available only with Multi-function and rotative system - 03945 ,00

☐ One piece aluminium footplate - Flip-up! rake and depth adjustable
Not available with Elevating front frame, swing away and removable
Minimum footplate distance 29cm. ☐ Internal ☆ 2/3 Internal ☐ 2/3 External ☐ External



11528

☐ One piece Carbon fibre footplate rake adjustable, swing away, flip-up.
Not available with Elevating front frame, swing away and removable
Minimum footplate distance 29cm. ☆ Internal ☐ External



03291

Mudguard

Mudguard - FIXED

☆ ABS mudguard

☐ ABS Straight sideguard



O Carbon fibre mudguard **03946**
O Carbon fibre Straight sideguard **08918**

Mudguard - REMOVABLE

O Removable ABS mudguard **08921**

O Removable ABS fibre straight sideguard **08921**



O Removable carbon fibre mudguard **08919**

O Removable Carbon fibre straight sideguard **08920**

Armrests

Tubolar armrests - Steel support with safety locking system
(Swing away, removable and height adjustable armrest)



00694

Removable armrest with ABS mudguard

O Desk armrests PROGEO **(Removable and height adjustable)**



09956

O Removable armrest with ABS straight sideguard **08881**



O Removable armrest with carbon-fiber straight sideguard **08882**

Optional 1

Only two optional devices for side can be chosen

O Transit wheels



00836

O Anti-tipper with rapid hookup **(inside rotation to reduce the encumbrance)**
O Right **00023**
O Left **00024**



O Tipping aid
O Right **00025**
O Left **01046**



O Crutches support
O Right **00838**
O Left **00837**




Date ..... Order ..... User ..... Address .....

Accessories

○ Pad for front frame protectors		**07058**
○ Backrest-seat connection cloth		**10241**
○ Removable storage bag (with quick coupling)		**09811**

Optional 2

○ Tetraclip	**(Quick release axle for quadriplegic)**		**03947**
○ Push handles for companion	**(Removable and height adjustable)**		**01048**
○ Harness			**04103**
○ Safety pelvic belt			**03972**
○ Tray table (removable)			**00508**
○ Lumbar support	**(to insert in the backrest upholstery)**		**00013**
○ Super Head rest	**(Folding with the wheelchair)**		**04049**
○ Swing away lateral support **Not available with Posture backrest PHYSIO**	○ Right ○ Left		**02097** **02098**
○ Spoke guards Black	(22"-24")		**01043**
○ Spoke guards Transparent	(22"-24")		**00835**
○ Spoke guards Progeo design	(22"-24")		**00019**
○ Spoke guards Dragon	(22"-24")		**02106**

Additional Kit

○ 24" Off-road rear wheels	**Off-Road tyre - aluminium handrim (black colour)**	**03378**
○ 24" FAT rear wheels	**FAT tyre 3" - aluminium handrim (black colour)**	**09357**


Date ..... Order ..... User ..... Address .....

PHYSIO - Posture backrest
(Std. Backrest upholstery not provided)


Removable with quick release
Suitable for tubes with diameter 18÷26mm
Depth adjustment (4cm)
Angle adjustment (±18°)

○ AIR Carbon shell

not available for seat width 48

BACKREST HEIGHT	28		34		40	
Shell's shape	Lateral retaining wing A=high - R=regular					
	A	R	A	R	A	R
7,5 cm						
	☐	☐	☐	☐	☐	☐

○ POSTURE Aluminum shell

BACKREST HEIGHT	34	40	52
Shell's shape	Lateral retaining wing B=regular		
	R	R	R
7,5 cm			
	☐	☐	☐

Configuration DEEP with side support PAD (height adjustable)

○ Alluminum lateral with padded, breathable upholdstery.



Small (h 13cm)



☐ Right **10272**

☐ Left **10272**

Large (h 20cm)




☐ Right **10273**

☐ Left **10273**

SWING AWAY - Lateral support

Fixing and adjustment hardware complete with protection sleeve
Alluminum lateral with padded, breathable upholdstery.



○ Large (18x12) **05647**

○ Small (14x9) **05643**

○ Lateral support extension — Quantity (number pcs)..... **10271**

○ Lateral support extension — Quantity (number pcs).....

○ Small (14x9) **05642**

○ Large (18x12) **05646**

○ Headrest adjustable - Double ball mounting system
Available only with backrest Physio
Not available for backrest Physio AIR carbon shell

☐ Large (34x14)
☐ Small (28x14)




05648

Date Order User Address

Note

REFERENCE TABLES

1	Front height	
With closed frame (95°) max 5" caster		
Casters	Front height min.	max
3"	41	49
4"	42	50
5"	44	51
6"	48	52
The size of the fork will be defined only by Progeo in accordance with wheelchair final configuration.		

2	Rear height			
Rear frame	Rear wheels 22"	24"	25"	26"
CARBON 	min. 37 max 46	min. 39 max 48	min. 40 max 49	min 41 max 50

3	Footplate option	Footplate distance Frame Angle 110°	Frame Angle 95°
Plastic footrest		min. 30	min. 31
One piece footplate - Flip-up!		min. 28	min. 29
One piece footplate - Flip-up! , with multifunction rotative system		min. 23	min. 24
One piece aluminium footplate - Flip-up!		min. 28	min. 29
One piece Carbon fibre footplate		min. 28	min. 29
Calculated with the best configuration and with the footplates positioned on inside.			
IMPORTANT NOTICE! From the footplate to the floor minimum 4cm !! (Minimum Front height = DP + 4cm)			

4	Rear wheels
Model	Features
22" Ultra-light Progeo - Standard!	(not available in anthracite color)
24" Ultra-light Progeo - Standard!	(available for all coulors)
24" ULTRA-LIGHT PROGEO KEY SPORT	(silver hub, black rim and 16 spokes)
24" Ultra-light "Spinergy LX"	(silver hub, black rim and spokes)
24" Ultra-light "Spinergy LXL"	(black hub and rim, 18 white spokes) - (black hub, rim and 18 spokes)
24" Ultra-light "Octopus Fibre Wheel"	(silver hub, black rim and spokes) - (integrated aluminium/rubber handrim - encumbrance reduction up to 3cm. - all tyre)
24" Off-road	(colour: black) - (aluminium handrim - tyre Off-road)
25" Ultra-light "Spinergy LX"	(silver hub, black rim and spokes)
25" Ultra-light "Spinergy LXL"	(black hub and rim, 18 white spokes)
26" Progeo - Standard!	(colour: black)
26" Ultra-light "Spinergy LX"	(silver hub, black rim and 18 spokes)

Order Form - Progeo VARIO CARBON

Date ..... Order ..... User ..... Address .....

12" wheel - Motor 250W (750W maximum power)
14" wheel - Motor 1000W (1500W maximum power)



Color display with switcher
Maximum speed limit settable from display
5 speed levels selectable
10 display-selectable acceleration levels
Adaptive Cruise Control

Disc and electronic brake control lever
Motor brake (adjustable in 10 levels from the display)
Electronic brake with control bottom (adjustable in 10 levels from the display)
Power regain when braking

Error messages management from display (with error history)
Rear gear beeper
48V - 5.8 Ah battery Autonomy up to 25km
48V - 11.6 Ah Power plus battery Autonomy up to 50km
Battery charger 48V


Rear gear
USB port
Easle
Mudguard
Front spoiler with predisposition for FULL LED light

(Certified software)

○ **Mototronik** **10979**

Handlebar

☆ STANDARD controls




☆ Thumb accelerator and Disc and electronic brake control lever (Right)

○ Grip throttle and Disc and electronic brake control lever
○ Right **10913**
○ Left **10914**




○ **QUADRIPLEGIC controls** **10905**
Handlebar PUSH&PULL

☆ **MOTOTRONIK 12" wheel**
Motor 250W (750W maximum power)
Maximum speed according to law



○ **MOTOTRONIK 14" wheel** **10903**
Motor 1000W (1500W maximum power)
Maximum speed according to law



Battery





☆ 48V - 5.8 Ah battery *Autonomy up to 25 km*

○ 48V - 11.6 Ah Power plus battery *Autonomy up to 50 km* **10904**

Order Form - Progeo VARIO CARBON

Date ..... Order ..... User ..... Address .....

Accessories

○ Handlebar extension Adjustable from 15cm up to 23cm			**10907**
○ Motor unit facilitated unlock lever Recommended with handlebar for quadriplegic			**10915**
○ Additional FLY 48V - 2.9 Ah battery Autonomy up to 15km Approved for air transport			**10906**
○ FULL LED light (high intensity) Integrated in the spoiler			**10908**
○ Rearview mirror	○ Right ○ Left		**10909** **10909**
○ Basket (removable) - (with KLICKfix® attachment system)			**10912**
○ Removable front weight - (with KLICKfix® attachment system) (it increases the weight over the power wheel to improve traction)			**10910**
○ Travel bag			**10916**

Note

Wheelchair : Progeo VARIO CARBON - Rev. 2023.2	Prices - VAT excluded to be added to the price list

Send this page only if any optional have been chosen

☆	standard	(supplied if no requests are indicated)
☐	on request	(without extra charge)
○	optional	(cost to be added at the basic price)